INSTRUCTIONS FOR CONVERTING
CM-0310 PUSH BUTTON TO CK-0320 ROOM KEY

KIT NO. K026

1. Remove key barrel from your lock and cut the barrel, including flange, to 7/8" long (see Illustration).

NOTE: A. TUMBLERS FROM THE LOCK WILL NOT BE PUT INTO ROOM KEY CYLINDER.

B. KEY LOCK IS NOT PROVIDED DUE TO CUSTOMER KEY VARIATIONS.

2. Insert cut-off key barrel into room key cylinder, Item 1. Key cylinder, Item 1, may require additional reaming due to variation of vendors' barrels. Tighten set screws, Item 4, into room key cylinder (see Illustration).

3. Remove push button switch from the dispenser door extrusion. (Do not remove wires from the push button switch.) Attach push button switch to the push button switch mounting bracket, Item 2 (see Illustration).

4. Insert room key cylinder, Item 1, into hole vacated by the push button switch. Mounting screws, Item 7, split ring lockwashers, Item 8, flat washers, Item 13, and bracket, Item 3, to be set in line and screws to be applied into room key cylinder from inside of ice button box.

5. Attach the push button bracket, Item 2, (with ice button switch attached) to the key cylinder bracket, Item 3 (see Illustration).

6. The dispenser is activated by inserting the room key into the barrel and pushing against the push button. Adjust push button bracket, Item 2, as needed for proper operation.

7. Attach new label, Item 11.