K00051 KEY CARD KIT

Installation Instructions

PARTS LIST

Item	Quantity	Part Number	Description
1.	1	6311814	Alignment Plate
2.	1	6269914	Key Card Access Plate Weldment
3.	1	6270314	Access Switch
4.	1	8008063	Installation Instructions
5.	1	6640514	Access Switch Bracket Weldment
6.	1	2075763	Lead (Blue)
7.	1	2075773	Lead (Black)
8.	1	8106803	Wiring Diagram
9.	1	8132303	Label, Insert Room Key Card
10.	2	5023291	#6-32 x 1" lg. Machine Screw
11.	2	5544541	#6 Lock Washer
12.	2	5428781	#6 Hex Nut
13.	4	5544591	#8 Lock Washer
14.	4	5429061	#8 Hex Nut

1. Disconnect power.
2. Drill six 1/4" diameter holes through tan or black Cycolac door liner using the dimension shown on Sketch 1.

3. Cut out the material between the two middle holes, as shown on Sketch 1.
4. Insert the studs on the key card access plate into the four mounting holes from the front side.
5. Assemble the access switch assembly to the studs with the lock washers and #8-32 hex nuts.
6. Attach wiring diagram from kit over the existing wiring diagram located on the control box cover of the dispenser.
7. Pull the black lead off of the ice button switch and attach it to the short black lead (connected to the access switch). Tape over connection with electrical tape.
8. Attach the new blue lead (connected to the access switch) to the common contact on the ice button switch.
9. Connect power and test. Insert room key card into slot and then push ice button switch.

Manitowoc Ice, Inc.
2110 South 26 Street, P.O. Box 1720, Manitowoc, WI 54221-1720 USA
Telephone 920-682-0161, Fax - Sales: 920-683-7589, Service/Parts: 920-683-7585, Other: 920-683-7879
Web Site - www.manitowocice.com