Manitowoc®

INDIGO® NXT

50Hz

QuietQube® iF600C Remote Ice Cube Machine

Air-Cooled Ice Cube Machine with Patented CVD Technology®

Models

☐ IYF0600C



IYF0600C Ice Cube Machine - 230v/50hz/1



CVD Condensing Unit - 230v/50hz/1



IYF0600C
Ice Machine
on a D-570 bin

*Ice machine and bin sold separately

Standard Features

QuietQube Series Remote System consists of a remote condensing unit, interconnecting refrigerant lines, ice machine head section along with an ice storage bin, countertop dispenser, or floor dispenser. All ordered separately. QuietQube ice machine with CVD condensing unit is designed as a Manitowoc system and cannot be used with any other ice machine or remote condenser brand.

- **Space-Saving Design –** Up to 610 lbs. (277 kgs) daily ice production and only 30" (76.20 cm) wide.
- **easyTouch® Display**- New icon based touch screen takes the guess work out of owning and operating an ice machine.
- **Programmable Ice Production** – Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume and night time programming.
- **Easy to Clean Foodzone** – Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- **Intelligent Diagnostics** – provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- **Acoustical Ice Sensing Probe** – Unique patented technology allows for reliable operation in challenging water conditions and environments.
- **Avaiable LuminIce II Virus and Bacteria Inhibitor**- Controls viruses, bacteria, mold and yeast within the food zone to keep the machine clean longer. A new sanitation icon lets you know the operational status.
- **Active Sense** – insures consistent ice harvest in all environmental conditions. This software solution works in conjunction with the acoustical ice sensing probe improving reliability and performance.



Ice Shape



Half Dice
⅜" x 1⅛" x ⅞"
(.95 x 2.86 x 2.22 cm)

QuietQube® iF600C Remote Ice Cube Machine

Welbilt Deutschland GmbH
Auf der Weih 11
D - 35745 Herborn, Germany
Tel.: +49 27 72 58 050
welbilt.com.de

Welbilt Iberia, S.A.U
Textil, 6 – Pol.Ind. La Ferreria – 08110
Montcada i Reixac
Barcelona, Spain
Tel.: +34 902 20 10 69
welbilt.com.es

Welbilt UK
Ashbourne HouseThe Guildway,
Old Portsmouth RdGuildford GU3
1LRUnited KingdomTel.:
+44 1483 464900
www.welbilt.uk


Manitowoc®

50Hz

QuietQube® iF600C Remote Ice Cube Machine

iF0600C Ice Machine

Ⓐ Electrical Entrance (2) Options
Ⓑ Suction Refrigerant Shut-off Valve
Ⓒ Liquid Refrigerant Shut-off Valve
Ⓓ 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
Ⓔ 1/2" (1.27 cm) F.P.T. Ice Making Water Drain



Installation Note
Minimum installation clearance:
Top: 5" (13 cm)
Back: 5" (13 cm)
Sides: 5" (13 cm)

Shipping Weight: 155 lbs. / 70 kg

Ice Machine Electric

230/ 50/1 standard.
Total Amps: 1.1
Max. fuse size: 15 amps HACR-type circuit breakers can be used in place of fuses.

Specifications

Operating Limits:
Ambient Temperature Range:
40˚ to 110˚F (4.4˚ to 43.4˚C)
Water Temperature Range:
40˚ to 90˚F (4.4˚ to 32.2˚C)
Water Pressure Ice Maker Water In:
Min. 20 psi (137.9 kPA)
Max. 80 psi (551.1 kPA)

Refrigerant


R404A CFC- Free

Remote Air-Cooled Ice Machine

Model	Ice Shape	Ice Production 24 Hours		Power kWh/ 100 lbs. @90°Air/70°F*
		70°Air/50°F Water 21° Air/10°C Water	90°Air/70°F Water* 32° Air/21°C Water	
IYF0600C	half-dice	610 lbs.	551 lbs.	5.53
		277 kg	250 kgs	
Water usage/100 lbs./45.4 kgs of Ice				
Potable Water: 20 gallons, 75.7 liters				

Ice machine for use with ice storage bin or ice dispenser and CVD condensing unit all ordered separately.
*kWh per 100 lbs. is total power of ice machine and condensing unit. Ice machine is 1 ph only. Condensing unit is 1 ph
This product is hermetically sealed and contains fluorinated green house gas R404a..

CVDF0600 Remote Condensing Unit




Ⓐ Electrical Entrance (2) Options
Ⓑ Optional Suction & Liquid Line Connections
Ⓒ Suction & Liquid Line Connections

Shipping Weight: 203 lbs. / 92 kgs

Condensing Unit Electric

230/ 50/1 standard. 50 Hz version of this model meets the international standard, IEC335-1, requirements for "tropical rating," the most severe duty rating an ice machine can obtain, (consult factory). HACR-type circuit breakers can be used in place of fuses. Note: QuietQube ice machine power supply is wired independent of CVD condensing unit.
Min. circuit ampacity: 11.6 1ph
Max. fuse size: 15 amps 1ph
HACR-type circuit breakers can be used in place of fuses.
BTU Per Hour: 11,800 (average) 13,700 (peak)
Compressor: Nominal rating: 1 HP
Operating Limits:
Ambient Temperature Range:
-20˚ to 130˚F (-29˚ to 54˚C)
Installation Information and Dimensions:
Maximum Line Length
—100' (30.5 m).*
Maximum Vertical Rise*
—35' (10.7 m) above ice machine.
Maximum Vertical Drop
—15' (4.5 m) below ice machine.
Minimum Installation Clearance
—Top/sides: 0" (0 cm)
—Back/Front: 48" (122 cm).



*A rise over 20' (6 m) requires S-Trap Kit K-00172 - ordered separately.

Indigo NXT Remote Tubing Kits

Model	Line Length		Weight	
	ft.	m	lbs.	kg
RC-21	20	6	12	5
RC-31	30	9	17	9
RC-51	50	15	27	13

Accessories

LuminIce® II Virus and Bacteria Inhibitor
controls viruses and bacteria inside the ice machine.



External Scoop holder
protect the ice scoop with the NSF approved versatile scoop holder.



Arctic Pure® Plus Water Filters
reduce sediments and chlorine contaminants down to .5 microns. Use with a Pre-filter is recommended.



6703C 50Hz 06/22

Manitowoc Ice reserves the right to make changes to the design or specifications without prior notice.

Welbilt Deutschland GmbH
Auf der Weih 11
D - 35745 Herborn, Germany
Tel.: +49 27 72 58 050
welbilt.com.de

Welbilt Iberia, S.A.U
Textil, 6 – Pol.Ind. La Ferreria – 08110
Montcada i Reixac
Barcelona, Spain
Tel.: +34 902 20 10 69
welbilt.com.es

Welbilt UK
Ashbourne HouseThe Guildway,
Old Portsmouth RdGuildford GU3
1LRUnited KingdomTel.:
+44 1483 464900
www.welbilt.uk